

Application S/N 10/701,749
Amendment Dated: February 12, 2007
Response to Office Action dated: September 5, 2006

CE11700JEM

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) A method for adjusting power consumption in a device, the method comprising the steps of:

in response to an emergency mode situation, receiving a command to enter a low power mode; and

adjusting, in response to receiving the command, at least one operating mode of the device so as to enter a low power operating mode ~~without affecting the voice transmission capabilities of the device during the low power operating mode~~ that still supports message exchange of the device but disables or alters features of the device not necessary to the operation of the device.

2. (previously presented) The method according to claim 1, wherein in the adjusting step, the at least one operating mode includes a quality of service setting, a vocoding ratio, a BER threshold that initiates background scanning, a frequency of monitoring other communications networks, a definition of a function key, an operating mode of a display, a resolution of a display, a sensor, a CPU clock speed, or an alert time.

3. (original) The method according to claim 1, further comprising the steps of:
receiving a second command to exit the low power mode; and
adjusting, in response to receiving the second command, the at least one operating mode of the device so as to exit the low power operating mode.

Application S/N 10/701,749
Amendment Dated: February 12, 2007
Response to Office Action dated: September 5, 2006

CE11700JEM

4. (original) The method according to claim 1, further comprising the step of preventing a user from changing the at least one operating mode while the device is in the low power operating mode.
5. (original) The method according to claim 1, further comprising the step of providing at least one status indicator for indicating at least one of an emergency situation and that the device is operating in the low power operation mode.
6. (previously presented) The method according to claim 1,
wherein the command is part of an alert message that also includes a uniform resource locator, and the method further comprises the step of presenting information associated with the uniform resource locator.
7. (original) The method according to claim 1, wherein the adjusting step comprises:
presenting a user with a plurality of operating modes;
accepting an input from the user that indicates a selected operating mode that is chosen from the plurality of operating modes; and
placing the device into the selected operating mode.
8. (original) The method according to claim 1, further comprising the step of continuing to operate the device after a battery energy level has fallen below a normal operating threshold.

Application S/N 10/701,749
Amendment Dated: February 12, 2007
Response to Office Action dated: September 5, 2006

CE11700JEM

9. (original) The method according to claim 1, further comprising the steps of:
monitoring an energy level of a battery;
comparing the energy level to a threshold;
transmitting an indication of the energy level to a central controller; and
providing an indication that the indication of the energy level has been transmitted.
10. (original) The method according to claim 1, further comprising the steps of:
monitoring an energy level of a battery;
comparing the energy level to a threshold;
transmitting an indication of the energy level to a central controller; and
providing an indication of an estimated time of arrival of a replacement battery.
11. (cancelled)
12. (original) The method according to claim 1, wherein the command to enter the low power mode is initiated by a user of the device.
13. (original) The method according to claim 1, wherein the command includes a receiver identification, and the method further comprises the step of determining if the receiver identification matches an identification associated with the device.

Application S/N 10/701,749
Amendment Dated: February 12, 2007
Response to Office Action dated: September 5, 2006

CE11700JEM

14. (previously presented) The method according to claim 13, wherein the receiver identification comprises a location description, and the determining step comprises comparing the location description to a current location of the device, wherein an event that causes the emergency mode situation at least partially occurs in the location description.

15. (currently amended) An electronic device comprising:

a receiver for receiving, in response to an emergency mode situation, a command to enter a low power mode; and

a mode controller communicatively coupled to the receiver, the mode controller being capable of adjusting at least one operating mode of the device so as to enter a low power operating mode when the command is received by the receiver ~~without affecting the voice transmission capabilities of the electronic device during the low power operating mode~~ wherein the low power operating mode still supports message exchange of the device but disables or alters features of the device not necessary to the operation of the device.

16. (previously presented) The electronic device according to claim 15, wherein the at least one operating mode includes a quality of service setting, a vocoding ratio, a BER threshold that initiates background scanning, a frequency of monitoring other communications networks, a definition of a function key, an operating mode of a display, a resolution of a display, a sensor, a CPU clock speed, or an alert time.

Application S/N 10/701,749
Amendment Dated: February 12, 2007
Response to Office Action dated: September 5, 2006

CE11700JEM

17. (original) The electronic device according to claim 15, wherein the receiver is further able to receive a second command to exit the low power mode, and
the mode controller is capable of adjusting the at least one operating mode of the device so as to exit the low power operating mode when the second command is received by the receiver.

18. (original) The electronic device according to claim 15, wherein the mode controller prevents a user from changing the at least one operating mode while the device is in the low power operating mode.

19. (original) The electronic device according to claim 15, further comprising at least one status indicator for indicating at least one of an emergency situation and that the device is operating in the low power operation mode.

20. (previously presented) The electronic device according to claim 15, wherein the command is part of an alert message that also includes a uniform resource locator, and the electronic device further comprises a display for presenting information associated with the uniform resource locator.

21. (original) The electronic device according to claim 15, wherein the mode controller is capable of:

presenting a user with a plurality of operating modes;

Application S/N 10/701,749
Amendment Dated: February 12, 2007
Response to Office Action dated: September 5, 2006

CE11700JEM

accepting an input from the user that indicates a selected operating mode that is
chosen from the plurality of operating modes; and
placing the device into the selected operating mode.

22. (original) The electronic device according to claim 15, further comprising:
means for monitoring an energy level of a battery, comparing the energy level to
a threshold, and transmitting an indication of the energy level to a central controller; and
an indicator for indicating an estimated time of arrival of a replacement battery.

23. (cancelled)

24. (original) The electronic device according to claim 15, wherein in the low power
operating mode, the electronic device continues to operate after a battery energy level
has fallen below a normal operating threshold.

25. (original) The electronic device according to claim 15, wherein the command to
enter the low power mode is initiated by a user of the device.

26. (original) The electronic device according to claim 15, wherein the command
includes a receiver identification, and the mode controller determines if the receiver
identification matches an identification associated with the device.

Application S/N 10/701,749
Amendment Dated: February 12, 2007
Response to Office Action dated: September 5, 2006

CE11700JEM

27. (previously presented) The electronic device according to claim 26, wherein the receiver identification comprises a location description, and the mode controller compares the location description to a current location of the device, wherein an event that causes the emergency mode situation at least partially occurs in the location description.

28. (currently amended) The electronic device according to claim 27, wherein the location description comprises at a tower identification, a network identification, a zip code, an area code or a time zone.

29. (currently amended) A machine readable storage having stored thereon a computer program product comprising computer programming instructions executable by a device that cause the device to perform ~~for performing~~ the steps of:

in response to an emergency mode situation, receiving a command to enter a low power mode; and

adjusting, in response to receiving the command, at least one operating mode of the device so as to enter a low power operating mode ~~without affecting the voice transmission capabilities of the device during the low power operating mode~~ that still supports message exchange of the device but disables or alters features of the device not necessary to the operation of the device.

30. (original) The computer program product according to claim 29, wherein the adjusting step comprises:

Application S/N 10/701,749
Amendment Dated: February 12, 2007
Response to Office Action dated: September 5, 2006

CE11700JEM

presenting a user with a plurality of operating modes;
accepting an input from the user that indicates a selected operating mode that is
chosen from the plurality of operating modes; and
placing the device into the selected operating mode.

31. (original) The computer program product according to claim 29, further comprising computer programming instructions for performing the step of continuing to operate the device after a battery energy level has fallen below a normal operating threshold.

32. (original) The computer program product according to claim 29, further comprising computer programming instructions for performing the steps of:

monitoring an energy level of a battery;
comparing the energy level to a threshold;
transmitting an indication of the energy level to a central controller; and
providing an indication that the indication of the energy level has been transmitted.

33. (original) The computer program product according to claim 29, wherein the command includes a receiver identification, and the computer program product further comprises computer programming instructions for performing the step of determining if the receiver identification matches an identification associated with the device.

Application S/N 10/701,749
Amendment Dated: February 12, 2007
Response to Office Action dated: September 5, 2006

CE11700JEM

34. (previously presented) The computer program product according to claim 33, wherein the receiver identification comprises a location description, and the determining step comprises comparing the location description to a current location of the device, wherein an event that causes the emergency mode situation at least partially occurs in the location description.

35. (previously presented) The computer program product according to claim 34, wherein the location description comprises a tower identification, a network identification, a zip code, an area code or a time zone.

36. (currently amended) A method for controlling an electronic device, the method comprising the steps of:

receiving at least one of data and voice information from the device; and

in response to an emergency mode situation, transmitting a message to the device, the message including a command instructing the device to enter a low power mode to conserve power during the emergency mode situation, wherein the low power mode still supports message exchange of the electronic device but disables or alters features of the device not necessary to the operation of the electronic device without affecting the voice transmission capabilities of the device during the low power operating mode.